

OIL CLOSED HOSE REEL

FEATURES

- STURDY METALLIC STRUCTURE
- COMPACT DESIGN .
- HEAVY DUTY SPRING
- LONG LASTING STEAL HUB

EN.

The Piusi CLOSED HOSE REEL for oil, entirely Made in Italy, is the perfect solution for managing the dispense of any kind of lubricant. Its sturdy closed structure makes this equipment ready to be fitted on a wall or into an open cabinet.

PERFORMANCE

max	max				
60 BAR	12 M				
	bound				
OPERATING PRESSURE	HOSE LENGTH				





PACKAGING	
CODE	
WITH HOSE	
HC60121200A	
WITHOUT HO	OSE
HNC60121200	1

PACKAGING								
CODE	WE	IGHT		PACKAGING	N.BOXES/ EUROPALLET			
0002	KG	LBS	ММ	PCS/PALLET	PCS/BOX	×		
WITH HOSE								
HC60121200A	19	41,9	550X200X540		1	12	20	
WITHOUT HOSE								
HNC60121200	14,5	32,9	550X200X540		1	12	20	

FILTERING OIL MON		ACCESSORIES	MERCHANDISE	PIUSI ®
(A) AIR	A B D ANTIFREEZE BIODIESEL DIESEL	F G G FOOD GASOLINE GREASE F	K O U KEROSENE OIL AdBlue®	WATER WINDSCREEN
wherever you need the safety. PIUSI's products work in any condition. ROOF INSTALLATION	PIUSI's hose reels: they can without any problem ab are without a doubt design wall INSTALLATION	out functionality and	IN THE BOX REEL WALL MOUNT BRACKE INSTRUCTION MANUA DETAILS A ROLLS HOSE GUIDE	
MODEL CLOSE A 516 B 259 C 491 D 295 E 123 F 90 G 270 H 10,5 I 160		REEL FRONT / SIDE	SWIVEL SWIVEL MATERIALS • BODY: CAST IRON • HUB: SYNTHERED STEL • TUBE: RUBBER	EL

TECHNICAL DATA									
CODE	DESCRIPTION	FLUIDS TYPE	HOSE	MAX OPERATING PRESSURE	PRESSURE DROP	INTLET WITH S WIVEL	OUTLET HOSETAIL	HOSE MAX LENGHT BOUND	HOSE LENGHT
			BSP	BAR	BAR	BSP	BSP	м	м
WITH HOSE									
HA20151200A	OPEN HOSE REEL 1/2" + 12MT HOSE	0	1/2"	60	10 @ 30 L/MIN*	1/2" MALE	1/2" MALE	-	12
WITHOUT HOSE									
HNC60121200	CLOSE HOSE REEL 1/2"	0		60	10 @ 30 L/MIN*	1/2" MALE	1/2" MALE	-	12

(*) PRESSURE DROP FOR OIL 200 CST

OIL CLOSED HOSE REEL